



STOCK 4-CYLINDER RULES

1. Any car or truck that came from the factory with a single or dual cam 4 cylinder engine permitted.
2. Steel body must be used. Aftermarket replacement body components allowed but must be Steel. No aluminum bodies or body panels allowed.
3. Stock engine type that came in the car/truck must be run. **(No aftermarket blocks, heads, or intakes allowed this includes Esslinger & Other Performance Companies)** Engine modifications allowed but block, head, and intake must remain stock. **(No Exceptions)**
4. Aluminum heads permitted on engines that came from the factory with an aluminum head. **No aftermarket heads allowed.**
5. Fuel injection permitted on engines that came from the factory with fuel injection. **No aftermarket fuel injection allowed.**
6. Stock type intakes only. **No aftermarket intakes allowed.**
7. Aftermarket headers will be allowed.
8. All glass, mirrors, body molding and trim must be removed. All insulation and any other combustible material must be removed. Pedals must remain stock. Dash may be modified for roll cage clearance.
9. A box type 6 point roll cage of 1 1/2" X .095 wall minimum steel tubing is required. Roll cage legs must be welded to 1/8" plates, 4" X 8" minimum size. Truck frames may use a 2" X 3" tubing to construct a perimeter frame to attach roll cage and door bars. Doors on both sides must have 3 bars, 1 1/2" X .095 minimum. Passenger side may be an "X" but must have 3 bars. The roll cage must be a box over, behind and in front of driver. The hoop behind the driver must have a diagonal brace. Roof loop must have a center bar. Extra bracing inside the cockpit is allowed.
10. Doors must be welded or chained shut. Windshield must be replaced with heavy gauge wire mesh. 3 bars of 3/8" diameter must be welded to the roll cage in front of driver.
11. **Tow Hooks/Chains MUST be Securely Mounted on Front and Rear of car** to provide towing points.
12. Stock suspension only. Absolutely **NO** modified suspension components of any kind will be permitted. This includes weight jacks, adjustable rod ends, etc. Replacement bushings ok.
13. Strut towers may be reinforced. Right front hubs may be reinforced. Wheel centers may be reinforced. Larger wheel studs and nuts are recommended.
14. Street type radial tires only. Racing tires and recaps are strictly prohibited. Hoosier and American Racer tires prohibited.
15. 13" or 14" tires only on Rear-wheel Drive Cars. 13", 14", or 15" tires allowed on Front-wheel Drive Cars.

**** Anyone found with chemically altered tires, will be suspended for 3 races and will lose all their points accumulated up to that race. Anyone found a 2nd time with chemically altered tires will be suspended for the remainder of the season. If a Tire Sample is taken from any car out of the "A"-Main, the drivers money will be held until the tire sample has cleared the lab.**

16. Aftermarket wheels allowed. Maximum width is 8". Only 1 Bead Lock Wheel allowed per car. *(Right-Rear on Rear-wheel Drive & Right-Front on Front-wheel Drive Cars)*

17. Fuel cell in steel can, or steel tank may be securely mounted in trunk. It must have a firewall between the tank and driver. Must meet the safety approval.
18. Pump Gas or Racing Fuel is Okay. (**No Alcohol, Methanol, Nitrous**)
19. Battery must be securely fastened down, if in cockpit it must be completely enclosed. Must run battery master disconnect switch within reach of driver.
20. Racing seat mandatory. A quick release 5 point racing type seat belt is required. Seat and seat belts must mount to frame or roll cage, and meet safety approval.
21. Must wear approved helmet and fire suit.
22. Raceceivers and Transponders are MANDATORY at all events. (*Rentals are Available at track*)

RULE BOOK DISCLAIMER

1. *The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. No express or implied warranty of safety shall result from publications of or compliance with these rules and/or regulations. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator or official.*
2. *The race director shall be empowered to permit minor deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. No expressed or implied warranty of safety shall result from such alteration of specifications. Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is final.*

WE RESERVE THE RIGHT TO MAKE REVISIONS, IF NEEDED!