

2026 CROWN VIC RULES

LEGAL CARS

1. The **ONLY** cars legal for competitions are 1995 or newer Ford Crown Victoria, Ford Crown Victoria Police Interceptor, Mercury Marquis and Lincoln Town Car

BODY

1. Bumpers must remain STOCK with no Sharp Edges or Points. Covers may be removed.
2. Rear bumpers cannot be braced up in any way.
3. Tow chains or hoops are **required**.
4. Mirrors must be removed.
5. Hood and Trunk must have hood type pins for easy access. No Bolting Down.
6. Numbers on both doors and roof are required. Numbers must be at least 16"tall.
7. No Excessive gutting. 4 doors can be skinned to allow clearance for cage. Center post may be removed. Hood/Trunk/Roof/Quarters must remain stock. Magnet must stick. Rear firewall and speaker deck must be in place.
8. No rear spoilers allowed.
9. Plastic inner fenders may be removed.
10. Adding of weight of any kind not permitted.

ENGINE

1. Must Remain Entirely stock 4.6L SOHC Engine. No turbos, super chargers or

Nitrous allowed.

2. Intake manifold Must Remain Stock. Plastic type only, no all aluminum.
3. Air Filter box and intake tube Must Remain Stock. No CAI or cone type filters.
4. Absolutely NO adjustment to the ECM of any kind, Stock parameters must be in place when inspected. OBD port must be visible and functional.
5. Aftermarket / stand alone harness not permitted.
6. Exhaust manifolds ONLY. No headers.
7. Exhaust pipe must go beyond the driver and exit from the side or rear of the car
Muffler and Exhaust Components are NOT Required. Straight pipes under the car are legal.

DRIVELINE

1. Transmission must remain entirely stock.
2. Torque converter must remain stock.
3. Rear end must remain entirely stock.
4. Factor Ford Gear ONLY. 2.73, 3.27, 3.55, and 3.73 ratios are the only gear ratios legal.
5. You may lock the differential by use of locking device or welding rear spider gears.

SUSPENSION

1. No altering of the suspension including sway bar links. Must be same length.

Sway bars may be removed.

2. No Air Ride, No Cutting, No Heating and No Lowering of Springs.
3. Shocks and Springs can only be replaced by the same stock parts or OEM Replacements. No racing springs or shocks. No coilovers.
4. Upper / lower control arms (front & rear) must remain stock. No modifications or alterations. No adjustable parts.
5. Spring Rubbers and LEGAL and recommended in the Right Front Spring.
6. You may adjust Caster and Camber as factory adjustments allow however NO modification of factory suspension is permitted. Camber bolts permitted.
7. Watts link may be braced or replaced with non adjustable aftermarket for safety.
8. 4 Wheel brakes required. No shut off valves.

INTERIOR

1. Steering Column must remain STOCK. Addition of a Quick Release and racing wheel is permitted.
2. Dash must remain STOCK. All Airbags in the car MUST be removed.
3. Pedals must remain STOCK.
4. No decking or cockpit areas allowed.
4. All glass must be removed except for the windshield. Windshield can be left in or removed
5. Windshield must have 3 or more Solid Steel Vertical Bars in front of the driver. If windshield glass is left in, the bars must be inside the windshield
6. If car has a passenger seat, 3 or more Solid Steel Vertical bars must be in front of passenger. This is **REQUIRED**

ROLL CAGE

1. Must be minimum 4 point cage with 4 curved door bars on the driver's side. Straight bars can be **used** on the passenger side. If passenger seat is installed, Passenger side roll cage must mirror driver's side including 1/4" plate
2. Cage must be welded to the frame and not the floor pan.
3. **A** driver's door plate is required.

WHEELS AND TIRES

1. All Season Tires **ONLY**
2. The **ONLY** tire Sizes Legal are 235/55/17, 225/60/16 and 215/70/15. 3. No High Performance, Auto Cross, Snow, Studded, mud or Directional Tires Permitted.
4. No Soaking, Softening, Grooving, Siping or Needling of Tires.
5. Must use stock steel wheels. Stock steel or aluminum.
6. All 4 wheels must be the same size, offset and material.
7. No Wheel Spacers
8. No offset wheels on Cars 2001 and newer

FUEL TANK

1. **Must Remain STOCK** and in the stock position
2. Replacing with a Fuel Cell or anything other than the stock tank is **NOT permitted**.

BATTERY

1. Must remain stock location or moved to the Rear Passenger Floorboard
2. If moved, the battery must be enclosed in a battery box that is securely mounted to the frame
3. If battery is moved, an All Power Kill Switch is **required** to be placed behind the

driver within reach of safety officials standing outside of the car.

SAFETY EQUIPMENT

Safety equipment specifications listed below are listed as a guide and are only a minimum standard for both driver and passenger areas. These minimum standards may not be sufficient enough to protect a driver from injury or death from some incidents. It is the responsibility of the driver, car, owner and crew to ensure the safety equipment on the car is properly installed, working as intended, and is sufficient to protect the driver (and passenger) from any incidents that occur. This may include using safety equipment that goes above and beyond the minimum specifications and recommended equipment listed below.

SEATS:

A. Full containment type seats constructed of aluminum to the general design specifications of SFI 39.2 standards are highly recommended. Design should include comprehensive head surround, shoulder and torso support system, energy impact foam, and removable head foam. **MANDATORY FOR PASSENGER**

B. Up fitting a current seat with bolt on kits will be permitted with a seat manufacturer produced kit and a base acceptable to the seat manufacturer. Components should include comprehensive head surround, shoulder and torso support system, energy impact foam. Must be installed in accordance to seat manufacturer's instructions.

C. Seats must be used as supplied and instructed by the seat manufacturer with the exception of trimming the length of the left side head surround for the purpose of egress only. If the left side head surround is trimmed to a distance that is less than the most forward surface of the driver's helmet (usually the area crossing the chin) then a left side head net meeting the SFI 37.1 must be installed with quick release latch.

D. Seats must be mounted to a seat frame that is welded to the race car frame/ roll cage structure. Attaching points, angles, and materials for the seat frame and mounting of the seat to the seat frame must be in accordance to the seat manufacturer's instructions. No mounting to floor pans.

E. At minimum, a racing seat is **REQUIRED** and must be bolted to the cage, not the floor, with a minimum 3/8" grade 5 or Higher Bolts 2.

RESTRAINTS:

A. The use of 5, 6, or 7 point driver restraint system certified SFI Spec 16.1 or 16.5 is **REQUIRED. No Exceptions!** All driver restraint systems shall not be in excess of 3 years of age past the date of manufacture. The use of a 7 point driver restraint system is strongly recommended. All mounting points of the racing harness **MUST** be mounted properly in accordance with the manufacturer's instructions, and securely mounted to the cage with the use of grade 5 or better hardware.

WINDOW NETS:

A. Window Nets certified to SFI 27.1 are **RECOMENDED** and must be mounted in accordance with the manufacturer's instructions and technical director's satisfaction. Passenger side is **REQUIRED** if a Passenger seat is installed.

DRIVER WORN EQUIPMENT:

A. A helmet certified to Snell SA2010/ FIA-8860, Snell SA15/FIA8860, SFI 31.1/2010 or SFI 31.1/2015 is **REQUIRED**.

B. A driver suit certified to SFI Spec 3.2A/5 is **REQUIRED**

C. Gloves certified to SFI Spec 3.3/5 are **REQUIRED**

D. Socks and Shoes certified to SFI Spec 3.3 are **REQUIRED**

E. Head and Neck Restraint Devices/ Systems are HIGHLY recommended for driver. **REQUIRED for Passenger**

F. At all times during an Event (practice, qualifying, and competition), **if** used, drivers must connect their helmet to a head and neck restraint device /system certified to SFI Spec 38.1. The device/system must display a valid SFI Spec 38.1 label. The head and neck restraint device/system, when connected, must conform to the manufacturer's mounting instructions, and must be configured, maintained and used in accordance with the manufacturer's instructions.

COCKPIT AREA:

- A. No sharp or protruding edges in or around the cockpit, which would impede the driver's rapid exit from the car.
- B. Windshield screens recommended. Screens must be securely fastened.
- C. Flame retardant seat, roll bar, knee and steering pads or padding are recommended.
- D. On the Passenger's side a detachable dummy steering wheel or detachable grab bar recommended.

FIRE SUPPRESSION:

- A. An in car-Fire Suppression system is Highly Recommended.
- B. All race cars should be equipped with a thermally deployed automatic fire suppression system. The fire suppression system will consist of a DOT approved cylinder manufactured from aluminum or steel with a capacity of ten (10) lbs of fire extinguishing agent, steel or steel reinforced lines, and two(2) thermally active discharge nozzles.
- C. All systems must meet or exceed SFI 17.1 specifications.
- D. Systems must be fully charged with ten (10) lbs of DuPont FE-36, 3M NOVEC 1230, or Fire Aide and display a legible and valid SFI and manufacturer label depicting fire extinguishing agent, capacity, and certification date. Cylinders that or beyond useful certification date must be inspected, serviced and re-labeled by the manufacturer.
- E. Cylinders must be mounted forward of the fuel cell. Cylinders must be securely mounted to the frame/roll cage assembly. The certification label must be unobstructed and easily accessible for inspection when the mounting is complete.
- F. The cylinder must be connected to the nozzles with steel or steel reinforced lines.
- G. Two (2) thermally activated nozzles must be used. One (1) nozzle must be located directly above the fuel cell in the fuel cell area and second nozzle must be located in the drive cockpit area.
- H. An optional manual override cable may be added to the system.

I. Drivers (and passengers, if applicable) under the age of 18 are REQUIRED to have a HEAD SOCK, window net, gloves and either a neck collar or a head and neck restraint system in addition to all other required safety equipment in place.

RULE BOOK DISCLAIMER

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules.

No express or implied warranty of safety shall result from publications of or compliance with these rules and/or regulations. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator or official.

The race director shall be empowered to permit minor deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements.

No expressed or implied warranty of safety shall result from such alteration of specifications. Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is FINAL.

**** NO GREY AREA. IF ITS NOT LISTED ITS NOT ALLOWED.****

**** RULES MAY BE MODIFIED AT ANY TIME TO KEEP CLASS FAIR AND AFFORDABLE****

RULE BOOK DISCLAIMER

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. No express or implied warranty of safety shall result from publications of or compliance with these rules and/or regulations. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator or official.

The race director shall be empowered to permit minor deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. No expressed or implied warranty of safety shall result from such alteration of specifications. Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is FINAL.

Revised 12/24